

**Rvs rond staf**



Afmeting		koudgetrokken DIN671 h9			warmgewalst DIN1013/7527		
rond mm	kg/m	303	304	316L	303	304	316L
3	0,06	x	x	x			
4	0,10	x	x	x			
5	0,16	x	x	x			
6	0,22	x	x	x		x	x
7	0,30	x	x	x		x	x
8	0,40	x	x	x		x	x
9	0,50	x	x	x		x	x
10	0,62	x	x	x		x	x
11	0,75	x	x	x		x	x
12	0,89	x	x	x		x	x
13	1,05	x	x	x		x	x
14	1,22	x	x	x		x	x
15	1,40	x	x	x	x	x	x
16	1,59	x	x	x	x	x	x
17	1,79	x	x	x		x	x
18	2,01	x	x	x	x	x	x
19	2,24	x	x	x	x	x	x
20	2,48	x	x	x	x	x	x
21	2,73	x	x	x			
22	3,00	x	x	x	x	x	x
24	3,57	x	x	x	x	x	x
25	3,88	x	x	x	x	x	x
26	4,19	x	x	x			
28	4,86	x	x	x	x	x	x
30	5,58	x	x	x	x	x	x
32	6,35	x	x	x	x	x	x
35	7,60	x	x	x	x	x	x
36	8,04	x	x	x	x	x	x
38	8,95	x	x	x	x	x	x
40	9,92	x	x	x	x	x	x
45	12,56	x	x	x	x	x	x
50	15,50	x	x	x	x	x	x
55	18,76	x	x	x	x	x	x
60	22,32	x	x	x	x	x	x
65	26,20	x	x	x	x	x	x

